

## ZeroFlush<sup>®</sup> Urinal



## **Description:**

ZeroFlush<sup>®</sup>, zero water urinals, are the culmination of proven technology, environmental concern and innovation. The patented system will provide you years of superior odor free performance and trouble free operation, improving total rest room sanitation and hygiene. ZeroFlush® has been developed to be the most economical and environmentally friendly zero water consuming urinals in the global market.

Model #: 101

The ZeroFlush® urinals can be used with either Pūrleve's 'Liquid Odor Barrier System' or Pūrleve's EnviroSeal™ system (either J-Trap or Elastomer) All ZeroFlush® urinals come equipped with the following items to allow for complete installations:

Mounting Hardware

- Wall Bracket
- Drain Flange Coupler Odor Barrier Liquid or EnviroSeal<sup>™</sup> System
- ZeroFlush® Insert Key
- Drain Insert
- Installation and Maintenance Instructions

## Characteristics:

- · Largest built-in waste trap of any no water urinal
- Averages 15,000 uses or an estimated 6 months
- before any maintenance
- No Cartridges
- Free of odor
- · Easiest to maintain and clean
- Lowest operational and maintenance cost
- No water or sewer cost

Applications:

- Ouickest return on investment
- Improved design reduces splash


- · Easy installation and retrofitting Water efficiency LEED<sup>™</sup> point accumulation
- Vitreous china and stainless steel
- No Leaky Valves
- No Hard Water Stains
- Eliminate Wasteful Flushing
- Eliminate Overflows
- Eliminate Flooding
- No Harsh Chemicals

o Educational Facilities o Government

o Healthcare Facilities

o Clean Rooms

19-3/4" (502mm) 8 (203mm) 27-1/2" C/L (698mm) 17-1/2 (445mm)



hygiene and odor. The ZeroFlush® and Pūrleve™ systems are located in the following areas:

## **Technical Data:**

ZeroFlush® Product ZF-101 Vitreous China No-Water Wall Hung Urinal with integral housing and drain insert. Dimensions: 19"W x 28"H x 15.5"D Non-ADA Rough-In: For 24" lip height, drain center line must be 17" from floor ADA Rough-In: For 17" lip height, drain center line must be 9.5" from floor Approximate Weight: 60 lbs. Color: White

As with any other urinal (water and no water), ZeroFlush® urinals should be cleaned on a regular basis.

Daily Cleaning:


Visitors, Employees and Customers for all washrooms no longer need to waste expensive water (if available) while sacrificing

The ZeroFlush® urinals are designed with the maintenance person in mind. Cleaning is very quick and easy.

NO scrubbing with detergents is required or the use of odor masking devices or chemicals.

Meets ASME A112.19.2-2008 and ASME A112.19.19-2006 for Nonwater Consuming Vitreous China Urinals as referenced in both the UPC and IPC.

IAPMOIGC 161-2000 and ANZIZ125.9-94



111 W. Olive Street Milwaukee, WI 53212 USA

TELEPHONE 1.877.PURLEVE 1 877 787 5383 407 935

INTERNET www.purleve.com www.zeroflush.com

